

DANOFLOOR SL AS



Epoxy Based Antistatic Self Levelling Floor Compound

DESCRIPTION

DANOFLOOR SL AS is five-component epoxy based antistatic self-levelling flooring system.

ADVANTAGES

- Antistatic system
- Aesthetically attractive
- Seamless system
- Good chemical and abrasion resistance
- Does not encourage microbial growth
- Non-dusting easy to maintain system

USES

DANOFLOOR SL AS is preferred flooring system for use on floors requiring clean and easy to maintain, electro static conductive flooring coupled with high abrasion and chemical resistance in various industries, which includes:

- Air-traffic control rooms and flight deck on ships
- Ammunitions AND Pyrotechnics production units
- Optical lenses and photographic production units
- Medical equipment units
- Electronic production areas and assembly shops
- Nuclear power plants
- Synthetic fibre processing mills
- LPG bottling and filling plant
- Areas handling flammable and explosive goods
- Operation theatres & recovery rooms

APPLICATION INSTRUCTIONS

The application of anti-static self-levelling epoxy flooring system includes, surface preparation, application of primer, connection to the earthing system, application of conductive base coat and finally application of epoxy self-levelling flooring to complete the system.

SURFACE PREPARATION

The surfaces must be sound, clean, dry, and free from cracks, undulations, oil, grease, laitance and loose particles.

New concrete surfaces should be minimum 28 days old and should be sound with tensile strength >1.5 mPa and moisture content <4%.

SURFACE PRIMING

Apply **DANOFLOOR PRIMER EP** epoxy-based primer @ 6 to 8 m²/Kg., on well prepared substrate covering the entire area uniformly. Allow the primer to dry. On absorbent or porous surface, it is necessary to apply second coat of primer. (Refer TDS of DANOFLOOR PRIMER EP for details).

CONNECTION TO EARTHING SYSTEM

Over the dried primer coat, self-adhesive copper tape, preferably 12 to 25mm width is laid @5mtr. c/c, by removing the release film from the tape bottom and sticking it to the surface by pressing the tape against the support and smoothening from the centre to the edges to drive out entrapped air.

The copper tape is then connected to earthing system by providing a copper plate at the junction of floor and wall in "L" shape and connecting the tape to the horizontal face of plate, the vertical end of plate is connected to earthen wire thereby completing the earthing system.

CONDUCTIVE BASE COAT

Apply two-component aqueous epoxy based anti-static coating **CONDUDAN** by brush or roller @ 8 to 10 m²/Kg., covering the entire area uniformly. Allow the conductive coat to dry.

Water up to 10% can be added to the mix to maintain the application consistency of conductive base coat. (Refer TDS of CONDUDAN for details).

ANTI-STATIC SELF-LEVELLING TOPPING

DANOFLOOR SL AS is supplied as pre-weighed five components. Prior to mixing of components, the Conductive Fibre shall be crushed by hand for easy dispersion in Hardener component.

The components of **DANOFLOOR SL AS** shall be mixed by taking **DANOFLOOR SL AS Hardener** component in a clean container followed by addition and gradual mixing of **DANOFLOOR SL AS Conductive Fibre** using slow speed heavy duty electric stirrer to achieve homogeneous lump free mix. Allow the mix to mature for 5 minutes.

In another clean container, pour the **DANOFLOOR SL AS Resin component** and add **DANOFLOOR SL AS Colouring Paste** gradually under continuous stirring until homogeneous mix and uniform colour is obtained. Add the previously mixed components (Hardener + Conductive Fibre) gradually under continuous stirring to obtain homogeneous mix. Finally add **DANOFLOOR SL AS Conductive Filler** component and mix until a homogeneous mixture is obtained.

The prepared mix of **DANOFLOOR SL AS** is spread using toothed serrated trowel and rolled using spike roller to remove air entrapment and avoid pin holes formation, while maintaining desired thickness.

Allow the applied system to cure for 24 hours before allowing foot traffic and cure for 7 days before subjecting the floor to vehicular traffic.

CLEANING

Immediately after application of **DANOFLOOR SL AS**, use suitable aromatic solvent for cleaning application tools.

APPLICATION DATA

Mix Ratio PBW (Resin: Hardener: Colouring Paste: Conductive Filler: Conductive Fibre)	100 : 55 : 7 : 210 : 0.34
Pot life at 30°C	40 to 80 Minutes
Curing Schedule Foot traffic/ Light load Full traffic load	24 to 48 Hrs 7 Days
Coverage per Pack @ 2mm	6 m ²

PROPERTIES OF APPLIED PRODUCT*

Properties	Values	Test Standard
Surface Resistance	8.6 X10 ⁴ Ω	ASTM F150/ BS 20050
Compressive Strength	>55N/mm ²	ISO 604
Flexural Strength	>40 N/mm ²	ISO 178
Tensile Strength	>20 N/mm ²	ISO 527
Bond Strength	35 Kg/cm ² (Concrete Failure)	ASTM D4541
Abrasion Resistance (CS10, 1000 Cycles)	<0.1gm.	ASTM D4060
Impact Resistance	>8 joules	ASTM D2794
Dry Heat resistance	80°C to 100°C	ASTM D2485
Scratch Resistance	No Failure @2.5Kg	BS 3900 Part E2

*Properties tested under laboratory condition for specimen cured @30°C for 15days. Properties may vary based on actual site conditions.

SUPPLY

DANOFLOOR SL AS is supplied in 18.60 Kg, pack. It has a shelf life of 12 months when stored under the covered shed in sealed condition.

Packing: 18.60 Kg.

Resin	Hardener	Colouring Paste	Conductive Filler	Conductive Fibre
5 Kg.	2.75 Kg.	0.35 Kg.	10.5 Kg.	0.017 Kg.

CHEMICAL RESISTANCE PROPERTIES*

No.	Chemical	Concentration	Observation
1.	Acetic acid	5%	Resistant
2.	Hydrochloric acid	20%	Resistant
3.	Sulphuric acid	50%	Resistant
4.	Nitric acid	10%	Resistant
5.	Phosphoric acid	30%	Resistant
6.	Salt solution	Concentrated	Resistant
7.	Sodium hydroxide	30%	Resistant
8.	Water	-	Resistant
9.	Lactic	10%	Resistant
10.	Citric acid	10%	Resistant
11.	Petrol	-	Resistant
12.	Oil	-	Resistant
13.	Fruit juice	-	Resistant

*Tested @ 25 to 35°C for 6 months immersion

STORAGE

DANOFLOOR SL AS must be stored above 5°C. Store under the shed & protect from extremes of temperature, heat, direct sunlight, and children.

SAFETY PRECAUTIONS

As with all chemical products, care should be taken during use and storage of **DANOFLOOR SL AS**.

Disclaimer: TIKI TAR DANOSA warrants that each of its products will be manufactured in accordance with the specifications in effect on the date of manufacture. While TIKI TAR DANOSA endeavors to ensure that information given herein is correct to the best of our knowledge, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation of information given by it. We recommend that adequate tests be performed by you to determine if this product meet all of your requirements.

Note: Properties subject to change as per specific requirement. Field service where provided does not constitute supervisory responsibility. Suggestions made by TIKIDAN either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not TIKIDAN, are responsible for carrying out procedures appropriate to a specific application. TIKIDAN reserves the right to amend the composition of its material and consequently their prices, without prior notice. For this reason, all orders will be accepted only in accordance with the conditions and technical specifications in force at the date of order

TIKITAR DANOSA (INDIA) PRIVATE LIMITED

Tiki Tar Estate, Village Road, Bhandup (W), Mumbai - 400 078,
Maharashtra, India. T: +91 22 4126 6699
E: info@tikidan.in | W: www.tikidan.in

