

# TIKI TAPE BI-ADHESIVE



## Double Side Pressure Sensitive Adhesive Sealing Tape

### DESCRIPTION

**TIKI TAPE BI-ADHESIVE** sealing tape is specially fabricated heavy duty, easy to install double sided, reinforced pressure sensitive tape.

The tape has two layers of pressure sensitive adhesive which bond respectively to the sand and HDPE membrane surface.

The specially developed adhesive layers work together to form a continuous and integral water tight seal at the laps.

### USES

- **TIKI TAPE BI-ADHESIVE** sealing tape is an 80mm wide tape used in water tight detailing on both horizontal and vertical waterproofing applications on retaining walls, basements, under-slabs, mud-slabs etc., using **TIKI HYDROSEAL** range of HDPE fully bonded waterproofing membrane in edges, penetrations, corners, tie-ins, etc., including end laps.
- It is also used to patch damaged areas in the **TIKI HYDROSEAL** range of HDPE fully bonded waterproofing membranes.

### APPLICATION

**TIKI TAPE BI-ADHESIVE** is pre-applied to the **TIKI HYDROSEAL** range of fully bonded waterproofing membrane and also field applied as needed.

### SURFACE PREPARATION

All surfaces to which the **TIKI TAPE BI-ADHESIVE** double sided tape will be applied to must be sound and stable, with an even finish and free from sharp protruding items, dust, loose debris, grease, curing agents, or anything else that might damage or prevent the proper adhesion / installation of tape.

Do NOT install the tape if raining or precipitation is imminent. Do not proceed with installation, if the surfaces are damp or wet. All surfaces must be completely dry to ensure proper adhesion of tape.

All unsatisfactory areas shall be repaired prior to final acceptance.

### End Overlaps of TIKI HYDROSEAL membrane

Keep the **TIKI TAPE BI-ADHESIVE** clean and protect it from being contaminated from dust, water before use.

After applying the **TIKI HYDROSEAL** range of HDPE fully bonded waterproofing membrane, unroll the tape and remove one side of release liner and adhere to the end laps of **TIKI HYDROSEAL** membrane. Use heavy hand pressure or a hand roller to maximize adhesion. Then remove another side of the release liner on **TIKI TAPE BI-ADHESIVE** and overlap with end lap of the subsequent **TIKI HYDROSEAL** membrane. Again use heavy hand pressure or a hand roller to maximize adhesion and ensure water tight seal.

The applied **TIKI TAPE BI-ADHESIVE** must be covered with **TIKI HYDROSEAL** range of HDPE waterproofing membrane the same day it is installed.

### SUPPLY

Overall Thickness: 0.8mm

Thickness(adhesive layer): 0.75-0.78mm

Roll size: 80mm (width) x: 20m (length)

### STORAGE

**TIKI TAPE BI-ADHESIVE** must be stored above 5°C. Store under the shed & protect from extremes of temperature. Do not store in direct sunlight or where they may be damaged by water or rain.

## SAFETY PRECAUTIONS

As with all synthetic products, care should be taken during use and storage of **TIKI TAPE BI-ADHESIVE**.

**Disclaimer:** **TIKI TAR DANOSA** warrants that each of its products will be manufactured in accordance with the specifications in effect on the date of manufacture. While **TIKI TAR DANOSA** endeavors to ensure that information given herein is correct to the best of our knowledge, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation of information given by it. We recommend that you to determine if this product meet all of your requirements perform adequate tests.

**Note:** Properties subject to change as per specific requirement. Field service where provided does not constitute supervisory responsibility. Suggestions made by **TIKIDAN** orally or in writing may be followed, either modified or rejected by the owner, engineer or contractor since they, and not **TIKIDAN**, are responsible for carrying out procedures appropriate to a specific application. **TIKIDAN** reserves the right to amend the composition of its material and consequently their prices, without prior notice. For this reason, all orders will be accepted only in accordance with the conditions and technical specifications in force at the date of order.

## **TIKITAR DANOSA (INDIA) PRIVATE LIMITED**

Tiki Tar Estate, Village Road, Bhandup (W), Mumbai - 400 078,  
Maharashtra, India. T: +91 22 4126 6699

E: [info@tikidan.in](mailto:info@tikidan.in) | W: [www.tikidan.in](http://www.tikidan.in)

