

Acrylic Sealant

DESCRIPTION

TIKI ACRYSEAL is high quality one component acrylic sealant.

The specially formulated white thixotropic paste is ideal for sealing static gaps / cracks in interior / exterior surfaces up to 5mm width.

USES

- Used to fill cracks in concrete, masonry, precast blocks, brick linings etc.
- Used to fill gaps between various substrates such as sliding windows, wooden frames, doors, baseboards etc.
- Used to fill joints of G.I / cement pipes, reinforced cement sheets, G.I sheets, gutters, flashing etc.
- Used to fill 'J' bolts of reinforced cement roofs
- Used to stop leakage around bathtubs, washbasins, kitchen sinks, platforms, ceramic, glass, metals, wood, concrete etc.

ADVANTAGES

- Single component
- Can be applied on damp surfaces
- Does not bleed or stain
- Can be painted over with conventional paint

PROPERTIES

Property	Value
Colour	White
Application	Spatula / Putty Knife
Initial Setting Time	4 to 6 Hours
Full Cure	48 to 72 Hours
Theoretical Coverage*	25 R.Mtr./ Kg. for 5mm Wide Gap

*Coverage is approximate and it depends upon the site conditions and surface porosity at the time of application.

APPLICATION INSTRUCTIONS

SURFACE PREPARATION

Ensure that all surfaces are clean, dry, and free from all loose dirt, dust, laitance, oil, grease, any other contaminants, which may impair adhesion of **TIKI ACRYSEAL**.

Metal surfaces should be cleaned and degreased.

For a neat finish, apply masking tape on both sides of joints/ cracks/gap and remove it before sealant has skinned over.

APPLICATION

Apply **TIKI ACRYSEAL** into the gaps/cracks/joints with a spatula or putty knife and level to get a smooth finish.

Ensure that the application is free from bubble or cavity formation.

CLEAN-UP

Use clean soap water for cleaning equipment and tools immediately after applying **TIKI ACRYSEAL**.

SUPPLY

TIKI ACRYSEAL is supplied in 200 gms tubes and 1 Kg. plastic container.

STORAGE

TIKI ACRYSEAL must be stored above 5°C. Store under the shed and protect from extremes of temperature. Keep container close when not in use.

SHELF LIFE

Shelf life is 12 months when stored as above and in original sealed container. Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging.

SAFETY PRECAUTIONS

As with all chemical products, care should be taken during use and storage of **TIKI ACRYSEAL** to avoid contact with eyes, mouth, skin, and foodstuffs until product is fully cured/dried.

Treat splashes to eyes and skin immediately. If accidentally ingested, seek immediate medical attention. Keep away from children. Reseal containers after use. Do not reuse containers for storage of consumable item.

VERSION: R1, 201901

Disclaimer: **TIKI TAR DANOSA** warrants that each of its products will be manufactured in accordance with the specifications in effect on the date of manufacture. While TIKI TAR DANOSA endeavors to ensure that information given herein is correct to the best of our knowledge, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation of information given by it. We recommend that adequate tests be performed by you to determine if this product meet all of your requirements.

Note: Properties subject to change as per specific requirement. Field service where provided does not constitute supervisory responsibility. Suggestions made by TIKIDAN either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not TIKIDAN, are responsible for carrying out procedures appropriate to a specific application. TIKIDAN reserves the right to amend the composition of its material and consequently their prices, without prior notice. For this reason, all orders will be accepted only in accordance with the conditions and technical specifications in force at the date of order.

TIKITAR DANOSA (INDIA) PRIVATE LIMITED

Tiki Tar Estate, Village Road, Bhandup (W), Mumbai - 400 078,
Maharashtra, India. T: +91 22 4126 6699
E: info@tikidan.in | W: www.tikidan.in

