

TIKICRYST 200



Low Dosage Economical Crystalline Waterproofing Admixture

DESCRIPTION

TIKICRYST 200 is advanced new generation hydrophilic crystalline waterproofing and permeability reducing concrete additive in dry powder form, effective in enhancing the concrete impermeability and durability by effectively sealing concrete pores and capillaries and reducing the shrinkage cracks.

Due to unique water reducing capability, It eliminates the need for using plasticizers / superplasticizers.

Its advanced chemistry enhances the hydration process in concrete increasing its ability to self-heal in presence of moisture upon micro-cracking and making concrete watertight.

TIKICRYST 200 admixture is free from stearates, silicates, chlorides and oils. When added to fresh concrete, the proprietary active components reacts with un-hydrated cement particles to form innumerable needlelike crystals filling the capillaries pores in concrete and reducing its size and numbers, thus making the concrete impermeable.

ADVANTAGES

- Allows concrete to withstands extreme hydrostatic pressure and enhances concrete durability.
- Reduces shrinkage cracks.
- Reduces water demand of concrete mix by 8% to 15%.
- Compatible with all grades of concrete.
- Imparts integral water tightness to structures.
- Protects reinforced concrete and hence steel from attack by waterborne corrosive chemicals such as sulphates, chlorides and corrosive salts.
- Self-seals static cracks up to 0.4mm.
- Permanently active technology - crystalline action is reactivated by contact with moisture or water.

- Equally effective against both positive and negative water pressure.
- Reduces efflorescence.
- Low dosage – economical.
- Protects concrete against water ingress through micro-cracks by autogenously healing all future micro-cracks.
- Aids concrete hydration process.
- More effective in smaller dosages – reduced dosage at higher cement content.
- Provides best quality to cost ratio in the industry.

USES

TIKICRYST 200 is use as crystalline waterproofing and permeability reducing concrete additive to provide permanent protection to all structural concrete that will be subjected to water pressure or remains in contact with water, such as:

- Below ground structures, basements, retaining walls, foundations, elevator pits
- Swimming pools, water tanks, & water reservoirs and other wet areas.
- Aquarium and water parks
- Structural and pre-cast concrete and pipes
- Marine structures
- Tunnels, dams, canals
- Bridge decks and parking decks
- Sewage and water treatment plants
- Podium and roof slabs

TIKICRYST 200 is also use as crystalline waterproofing admixture for cement mortars and plasters.

PROPERTIES

Colour	Grey
Appearance	Free flowing granular powder
Bulk Density	≈1450 Kg./m ³
Solids	100%

APPLICATION INSTRUCTIONS

TIKICRYST 200 is ready to use dry powder that may be added directly to the wet concrete mix during batching or added directly to the ready mix truck prior to arrival at the site.

It does not require pre-wetting or pre-mixing in to the slurry.

As **TIKICRYST 200** improves the workability of mix, it is preferable to reduce water demand of concrete mix by 8% to 15%, thus eliminating the need for additional use of plasticizer / superplasticizer.

Allow mixing for ≈5 minutes at high speed to ensure a homogeneous distribution of the product in the mix. Should addition of other admixture is required, add it after the addition of the product. Do not add water to the mix to increase slump.

DOSAGE

TIKICRYST 200 should only be used in concrete mix having cementitious material $\geq 300 \text{ Kg./m}^3$. It should be dosed @ 2 Kg./m^3 of concrete mix.

COMPATIBILITY

TIKICRYST 200 is suitable for use in concrete mixes prepared with all grades of cement and cementitious materials including slag and pozzolans.

It is compatible with most admixtures used in the production of quality concrete.

It is recommended to conduct site trial with the admixture in concrete mix to arrive at compatibility with various cementitious materials.

SUPPLY

TIKICRYST 200 is supplied in 25 Kg., pack size.

STORAGE

TIKICRYST 200 must be stored above 5°C. Store under the shed & protect from extremes of temperature, heat, direct sunlight. The shelf life is 12 months in sealed unopened container.

SAFETY PRECAUTIONS

As with all chemical products, care should be taken during use and storage. This product becomes alkaline when mixed with water, avoid contact with skin, eyes, mouth and food. For further detail, refer to Material Safety Data Sheet.

VERSION: R2, 202007

Disclaimer: The technical information, and, in particular, the recommendations relating to the application and end-use of Tiki Tar Danosa (TIKIDAN) products, are given in good faith based on TIKIDAN's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with TIKIDAN's recommendations. The information herein is of a general nature and no assumption can be made as to a product's suitability for a particular use or application and no warranty in respect of merchantability or of fitness for a particular purpose can be inferred from this information. The user alone is fully responsible for the product's suitability for the intended application and purpose. TIKIDAN reserves the right to change the properties of its products.

Note: Field service where provided does not constitute supervisory responsibility. Suggestions made by TIKIDAN either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not TIKIDAN, are responsible for carrying out procedures appropriate to a specific application. TIKIDAN reserves the right to amend the composition of its material and consequently their prices, without prior notice. For this reason, all orders will be accepted only in accordance with the conditions and technical specifications in force at the date of order. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

TIKITAR DANOSA (INDIA) PRIVATE LIMITED

Tiki Tar Estate, Village Road, Bhandup (W), Mumbai - 400 078,
Maharashtra, India. T: +91 22 4126 6699
E: info@tikidan.in | W: www.tikidan.in



ISO 9001:2015