

Hydro Injection Flange

DESCRIPTION

TIKIPLAN PTA is finishing element for synthetic liners made of polyvinyl chloride. **TIKIPLAN PTA** is ready to use accessories on base of PVC Geomembranes and compartment for waterproofing. **TIKIPLAN PTA** injection flange is to be mounted after membrane installation and prior to concrete works. It is used as control and injection element to control water tightness of completed basement or tunnel waterproofing with PVC Geo-membrane in each compartment of waterproofing. It is used as injection access to waterproof leaks in installed membrane system at any time after structural works are completed.



ADVANTAGES

- Easy and quick control of water tightness.
- Socket on base of plasticized PVC and compatible to all PVC Geomembrane by heat welding.
- Flexibility to low temperatures.
- High Puncture resistance.
- Excellent Weld ability.

USES

TIKIPLAN PTA is composed of a pre-formed valve made of the same type of material. This can be connected to injection pipe and injection connector to enables repair of compartmentalization system.

APPLICATION DATA

Property	Test	Value
Tensile strength ISO R527	ASTM D638	≥ 10 N
Ultimate Elongation ISO R527	ASTM D638	>200%

SUPPLY

TIKIPLAN PTA is supplied in round shape with smooth surface socket on top.

1Box: 100 Numbers

Size: 180 mm ± 5mm dia.

Color: White or grey

STORAGE

TIKIPLAN PTA must be stored above 5°C. Store under the shed & protect from extremes of temperature, heat, and direct sunlight.

SAFETY PRECAUTIONS

As with all synthetic products, care should be taken during use and storage of **TIKIPLAN PTA**.

VERSION: R4, 202203

Disclaimer: The technical information, and, in particular, the recommendations relating to the application and end-use of Tiki Tar Danosa (TIKIDAN) products, are given in good faith based on TIKIDAN's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with TIKIDAN's recommendations. The information herein is of a general nature and no assumption can be made as to a product's suitability for a particular use or application and no warranty in respect of merchantability or of fitness for a particular purpose can be inferred from this information. The user alone is fully responsible for the product's suitability for the intended application and purpose. TIKIDAN reserves the right to change the properties of its products.

Note: Field service where provided does not constitute supervisory responsibility. Suggestions made by TIKIDAN either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not TIKIDAN, are responsible for carrying out procedures appropriate to a specific application. TIKIDAN reserves the right to amend the composition of its material and consequently their prices, without prior notice. For this reason, all orders will be accepted only in accordance with the conditions and technical specifications in force at the date of order. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

TIKITAR DANOSA (INDIA) PRIVATE LIMITED

Tiki Tar Estate, Village Road, Bhandup (W), Mumbai - 400 078,

Maharashtra, India. T: +91 22 4126 6699

E: info@tikidan.in | W: www.tikidan.in

